

## E.S400 - TORQUE READING ELECTRONIC TORQUE SCREWDRIVERS




### Standards :

NF EN ISO 6789, ISO 6789, DIN EN ISO 6789

### Description :

- Accuracy:  $\pm 2\%$  clockwise ( $\pm 3\%$  counter clockwise) between 20% and 100% screwdriver capacity.
- Resolution: 0.1 cN.m.
- Measurement mode: tip or follower.
- 1/4" outlet with auto-locking system for series 1 and series 6 bits.
- Measurement unit: cN.m, in.lb, Kg.cm .
- 9 torque presets available.
- Memory 250 values with PC USB link.
- Locking keypad (program selection and result log only accessible to the operator).
- Hole in the handle for strapping when working in high places.
- Supplied with 1 AAA-LR03 1.5V battery.
- Supplied with an ISO6789 calibration certificate.
- Supplied in plastic case and foam module, dim. (L.xW.xH.): 570x100x70 mm.
- USB cable E.S404-USB and plugs E.S404-KIT set available as spares.

### References :

|  | L [MM] | CAPACITY [N.M] | [G] |
|---|--------|----------------|-----|
| E.S401  | 215    | 0,1 - 1        | 630 |
| E.S404  | 215    | 0,4 - 4        | 630 |