

306D - CLICK WRENCHES WITHOUT ACCESSORIES




Standards :

NF EN ISO 6789, ISO 6789, DIN EN ISO 6789

Description :

- Factory accuracy: $\pm 2\%$ except: - R.306-25D - K.306A600 - K.306A1000 ($\pm 4\%$). - R.304DA ($\pm 6\%$).
- Reliability of mechanism: 50 000 cycles (wrenches up to 200 N.m).
- Use possible with accessories: - End fitting: 9 x 12 or 14 x 18 mm. - Diameter: 30 mm.
- One-way wrenches usable for unscrewing by reversing the bits.
- Numbered wrenches supplied with ISO 6789 calibration certificate.
- Supplied in plastic box.

References :

	L [MM]	ATTACHMENT	BOX	CAPACITY [N.M]	GRADUATION [N.M]	[KG]
R.304DA	185	9 x 12	BP.102	1 - 5	0,05	0.29
R.306-25D	271	9 x 12	BP.D1	5 - 25	0,10	0.45
J.306-50D	357	9 x 12	BP.D2	10 - 50	1,00	0.93
S.306-100D	437	9 x 12	BP.D2	20 - 100	1,00	1
S.306-200D	515	14 x 18	BP.D3	40 - 200	1,00	1.3
S.306-350D	725	14 x 18	BP.D3	70 - 350	2,00	1.8
K.306-600D	945	14 x 18	BP.D600	120 - 600	2,00	4.6
K.306-1000D	1280	Ø 30 mm	BP.D1000	200 - 1000	4,00	5.9