

J-S.208A - CLICK WRENCHES WITH REMOVABLE RATCHET



Standards :

NF EN ISO 6789, ISO 6789, DIN EN ISO 6789

Description :

- Accuracy: $\pm 4\%$.
- Reliability of mechanism 25 000 cycles.
- End fitting: 9 x 12 or 14 x 18 mm for accessories (ratchets, polygon and open end bits).
- One-way wrenches usable for unscrewing by reversing the bits.
- Sensitive and sound click when reaching torque.
- Automatic reset.
- Supplied with ISO 6789 calibration certificate.
- Supplied in plastic protection tube with ratchet.

References :

	L [MM]	ATTACHME	CAPACIT [N.M]	SQUAR ["]	WRENC	RATCHET	CONTAINER	GRADUATI [N.M]	[K
J.208A50	337	9 x 12	10 - 50	3/8	J.208-50D	J.372V		0,5	0.7
S.208A100	396	9 x 12	20 - 100	1/2	S.208-100D	S.372V	Case: CKS.67SJ1	1,0	0.9
S.208A200	466	14 x 18	40 - 200	1/2	S.208-200D	S.382V	Roll: N.38A-9E	2,0	1.7
S.208A340	618	14 x 18	60 - 340	1/2	S.208-340D	S.382V	Box BP.39VA + Tray PL.206	2,0	1.4