

306D.SLS - CLICK WRENCHES WITHOUT ACCESSORIES



Standards :

NF EN ISO 6789, ISO 6789, DIN EN ISO 6789

Description :

- Tool equipped with a FACOM SLS attachment solution, preventing any risk of accidental falls.
- FACOM has adopted the shackle solution for particularly heavy and/or large tools (32 - 41 mm wrenches).
- Factory accuracy: $\pm 2\%$ except: R.306-25DSLS.
- Reliability of mechanism: 50 000 cycles (wrenches up to 200 N.m).
- Use possible with accessories: - End fitting: 9 x 12 or 14 x 18 mm. - Diameter: 30 mm.
- One-way wrenches usable for unscrewing by reversing the bits.
- Numbered wrenches supplied with ISO 6789 calibration certificate.
- Supplied in plastic box.

References :

	L [MM]	ATTACHMENT	BOX	CAPACITY [N.M]	GRADUATION [N.M]	[KG]
R.306-25DSLS	271	9 x 12	BP.D1	5 - 25	0,10	0.49
J.306-50DSLS	357	9 x 12	BP.D2	10 - 50	1,00	0.97
S.306-100DSLS	437	9 x 12	BP.D2	20 - 100	1,00	1.09
S.306-200DSLS	515	14 x 18	BP.D3	40 - 200	1,00	1.3
S.306-350DSLS	725	14 x 18	BP.D3	70 - 350	2,00	1.83