

## K.B 3/4" DRIVE METRIC 12-POINT SOCKETS




### Standards :

NF ISO 2725-1, NF ISO 1711-1, ISO 2725-1, ISO 1711-1, DIN 3124, ASME B107.5


### Description :

- OGV® profile: more powerful tightening, preserves fasteners.
- Secure attachment of plunger lock accessories
- Quick release button.
- Finish: satin chrome.



### References :

	A [MM]	D [MM]	D1 [MM]	L [MM]	L1 [MM]	12-POINT [MM]	COLOR	[G]
K.19B	19	36	30,1	51,0	14	12	Red 3020	207
K.21B	21	36	32,0	51,0	14	12	Black 9004	208
K.22B	22	36	33,4	51,0	14	12		221
K.23B	23	36	36,0	52,5	14	12		244
K.24B	24	36	36,0	52,5	16	12		237
K.26B	26	36	38,9	52,5	16	12		231
K.27B	27	36	39,7	52,5	18	12		232

	A [MM]	D [MM]	D1 [MM]	L [MM]	L1 [MM]	12-POINT [MM]	COLOR	[G]
K.28B	28	36	41,0	52,5	18	12		239
K.29B	29	36	42,0	52,5	18	12		245
K.30B	30	36	43,2	59,0	20	12		282
K.32B	32	36	45,9	59,0	22	12		301
K.33B	33	36	48,1	59,0	22	12		330
K.34B	34	36	48,4	59,0	24	12		322
K.35B	35	36	50,1	59,0	24	12		344
K.36B	36	36	51,0	59,0	24	12		347
K.38B	38	40	54,3	66,9	27	12		478
K.40B	40	40	56,0	66,9	27	12		493
K.41B	41	40	57,3	66,9	27	12		504
K.42B	42	40	59,5	66,9	27	12		552
K.43B	43	40	60,7	66,9	28	21		301
K.44B	44	40	61,9	66,9	28	12		587
K.46B	46	40	63,5	75,0	30	12		641
K.50B	50	40	68,5	75,0	33	12		725
K.54B	54	45	74,0	75,0	36	12		880
K.55B	55	45	74,7	75,0	36	12		875