


PNEUMATIC NEEDLE SCALER





Description:

• Straight and compact design allows easy operation even in hard to reach areas. • High performance motor delivers 4200 blows per minute for efficient working. • Tool used for aggressive material removal for example to remove rust. • Needle action great to work on irregular surfaces providing access to cracks or slots. • 3 mm needles available as accessory for rougher removal when needed. • Delivered with 27 needles diameter 2 mm with matching needle plate. • Blows per minute 4200 cpm. • Working pressure 6,2 bar. • Average air consumption 24 l/min. • Average air consumption 0,9 cfm. • Air inlet 1/4". • Minimum hose diameter 10 mm -3/8". • Vibration 11,7 m/s²/a. • Vibration 1,66 m/s²/K. • Sound pressure 94 dB(A). • Sound power 105 dB(A). • Available as accessories: (if changing needles, do not forget to order the needle plate accordingly) - Set of 27 needles diameter 2 mm: V.352FA1. - Needle plate for 2 mm needles: V.352FSAV16A. - Set of 12 needles diameter 3 mm: V.352FA1D3. - Needle plate for 3 mm needles: V.352FSAV16B.

References:

= 0	H [MM]	L [MM]	L1 [MM]	[KG]
V.352F	36	360	75	1.7

© FACOM 2020 1