

## 193A-195A.VE - 1,000 VOLT INSULATED SHORT HALF-ROUND NOSE PLIERS




### Standards :

NF ISO 5745, ISO 5745, DIN ISO 5745, ASME B107.500, NF EN 60900, EN 60900, DIN EN 60900

### Description :

- For your safety, all pliers are tested individually at 10,000 volts for 10 seconds, at the end of the manufacturing cycle.
- Narrow, finely serrated tips with side cutting edges.
- 193A.VE: straight nose. - 195A.VE: 40° angled nose.
- Cutting edges for copper and hard steel wire to a maximum specification of 1.6mm 160 kg/mm<sup>2</sup>.
- High durability carbon alloy steel, with induction hardened cutting edges.
- Bi-Material ergonomic grips resistant to chemical agents featuring: - Return spring - Tether ready (Tether point adds 10mm to nominal length)
- Varnish finish to help prevent rusting.

### References :

	B [MM]	C [MM]	D [MM]	E [MM]	E1 [MM]	L [MM]	160 KG/MM <sup>2</sup> [Ø MM]	CU - Ø MAX [MM <sup>2</sup> ]	[G]
193A.16VE	17	50	2,5	3	9	160	1,6	0,7 - 3,0	177
195A.16VE	17	50	2,5	3	9	160	1,6	0,7 - 3,0	177